

Skim coat compound

Description

SKIM COAT Compound is a water-based vinyl compound designed for smoothing and finishing wall surfaces. Available in ready-mixed and powder forms, the compound provides excellent slip to spread and dries to a fine surface. It is excellent for skim-coating concrete wall and panel surfaces. The compound offers good crack-resistance, excellent adhesion, and ease for working.

Uses

- Cement wall coat 、wood products 、cracks 、holes repairing
- Calcium silicate board 、gypsum board 、plywood 、all kinds of fireproof board 、and other priming and repairing

Features

quick dry, sandpapering, effortless

Color

White



Packing

Content

Polyvinyl acetate resin 、Calcium carbonate 、water

Product specification

20 Kg \pm 5 %

Original

Taiwan

Directions

1. Dust first, then wash if necessary to remove any grease. Use a sponge or a damp towel to wipe down the surface. Use water or a wall-friendly cleaning product depending on the extent of any grime. Rinse the wall with clean water after using any cleaning product.
2. You should only skim over matte paint or primer. Any other painted surface should be primed with a basic primer, then prepared by wiping down with a degreaser. This allows the compound to attach to the surface and not slide off or bubble. If you have removed wallpaper from a wall, prime the surface again with an oil-based primer.
3. Don't clean drywall tools over a drain. The compound will stick, harden, and block your pipes.

RAYSOUND BUILDINGS MATERIALS CORP.

TEL : +886-2-8696-1792 FAX : +886-2-8696-1505

